Pullman Sofa Technical Specifications

Testing

Our seating is designed to meet or exceed all EN performance requirements per **EN16139:2013**, which includes the following tests:

- Seat and back static load test
- Seat front edge static load test
- Vertical static load on back
- Foot rest and leg rest static load test
- Arm sideways static load test
- Arm downwards static load test
- Vertical upwards static load on arm rests

- Seat and back durability test
- Seat front edge durability test
- Leg forward static load test
- Leg sideways static load test
- Seat impact test
- Back impact test
- Arm impact test

Flammability

The cold cure foam material has been tested to meet the following standards:

British standard 5852:2006 Part 2

California Technical Bulletin **117-2013**

Italian standards

UNI 9175-CLASS 1.IM

The flammability standard of the covering fabric is dependent on the choice made by the customer, details of the flammability rating of specific fabrics can be found on supplier's websites listed below.

www.kvadrat.dk
www.camirafabrics.com
www.butefabrics.com
www.panaz.com
www.maharam.com
www.vescom.com
www.ultrafabricsllc.com
www.crestleather.com

Servicing




If a component is damaged and needs replacing then please email our team with an image of the damaged part and reference your order number, we will be happy to facilitate any replacements.

Warranty



naughtone offers a 10 Year warranty across all products Details on the terms and conditions of naughtones warranty can be found at naughtone.com/warranty

Pullman Sofa Technical Specifications



and I All dime quoted to the n	uct Code Description ensions are rounded learest 5mm est 1/2 inch	A Width	B Depth	C Height Overall	D Seat Height	E Seat Width	F Height from Seat to Top	G Surround Thickness	H Tablet Diameter	i Weight
1	PUL2H Pullman 2 Seat Sofa with Legs	1300 mm 51 in	675 mm 26.5 in	1300 mm 51 in	450 mm 18 in	1080 mm 42.5 in	850 mm 34 in	60 mm 2 in	350 mm 14 in	76 kg 168 lbs
2	PUL3H Pullman 3 Seat Sofa with Legs	1900 mm 75 in	675 mm 26.5 in	1300 mm 25.5 in	450 mm 18 in	1780 mm 70 in	850 mm 34 in	60 mm 2 in	350 mm 14 in	80 kg 177 lbs

